

**OLYMPIC Deck, Fence, Siding Solid Color Stain****GENERAL DESCRIPTION**

OLYMPIC Deck, Fence & Siding Solid Color Stain provides a beautiful, opaque finish that allows the wood texture to show through. Our formulation of 100% Acrylic resins guarantees OLYMPIC beauty and protection.

Recommended for use on exterior wood decks, fences, siding, railings, outdoor furniture and other wood surfaces. May be used on new wood, pressure-treated wood, weathered wood, and weathered stained or painted wood.

RECOMMENDED USES

Pressure-treated wood
Weathered wood
Wood decks
Wood siding

FEATURES / BENEFITS

WaterGuard® Waterproofing Protection
SunBlock® U.V. Protection
Exclusive Scuff Guard® Formula

APPLICATION INFORMATION

FOR EXTERIOR USE ONLY Stir thoroughly before and often during use. When using more than one can of the same color, intermix to ensure color uniformity.

Pretest: Test a small hidden area prior to application to ensure acceptable appearance and penetration.

Application Equipment: Apply with a high quality brush, roller, paint pad, or by spray equipment.

Application Method: Apply two coats. When spraying or rolling, always backbrush for best results. To help avoid lap marks, apply to only a few boards at a time keeping a wet edge.

Thinning: Do not thin.

PRODUCT INFORMATION

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

53201	White (Base 1)
53202	Base 2*
53203	Navajo Red
53206	Cedar
53207	Cape Cod Gray
53208	Russet

*Must be tinted before use.

Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

PRODUCT DATA

PRODUCT TYPE:	100% Acrylic
VOLUME SOLIDS*:	28% +/- 2%
WEIGHT SOLIDS*:	40% +/- 2%
VOC*:	<100 g/L (0.8 lbs./gal.)
WEIGHT/GALLON*:	10 lbs. (4.5 kg) +/- 0.2 lbs. (91 g)

*Product data calculated on 53201.

COVERAGE: Approximately 350 to 500 sq. ft. (32.5 to 46.5 sq. meters) per gallon (3.78 Liters) depending upon wood texture.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Normally dries in 30 minutes when applied in temperatures of 50°F (10°C) to 85°F (29°C). Allow 2 to 4 hours between coats or before recoating. High humidity or low temperature application may prolong drying and recoating times. It is not recommended to apply product if rain is expected within 24 hours. Allow 24-48 hours drying time for light foot traffic or furniture placement. Newly stained surfaces should be allowed to cure 30 days before washing.

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

CLEANUP: Clean brushes and tools with warm soapy water.

FLASH POINT: Over 200°F (93°C)

OLYMPIC Deck, Fence, Siding Solid Color Stain

GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the *OLYMPIC* limited warranty to apply. All surfaces must be clean and free of dirt, dust, oil, mildew, and other contaminants. Remove grade stamps, pencil marks, etc. by sanding.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

DECKS: Clean weathered, dirty or mildewed surfaces with *OLYMPIC* Deck Cleaner prior to applying product.

FENCES OR SIDING: Remove and inhibit mildew with *OLYMPIC* Mildew Check® Multi-Purpose Wash. Before use, be sure to read and follow the instructions and warnings on the label.

PRETEST: Test a small hidden area prior to application to ensure acceptable appearance and penetration.

PRIME: Priming not required. Two coats of this product are recommended for maximum protection to new wood surfaces. However when light or pastel shades of solid color stain are applied to wood with high extractives such as redwood, cedar or fir, *OLYMPIC* Alkyd/Oil Deck Primer, 53009, should be applied first to help retard potential extractive bleeding.

EXTRACTIVE BLEEDING: Some woods, such as redwood and cedar contain high amounts of tannin, a colored wood extract. The first coat of stain may show some color discoloration, but the tannins will be trapped in the first coat of stain. A second coat will result in a uniform appearance.

LIMITATIONS OF USE

Apply when air and surface temperatures are 35°F (2°C) or above and when the air and surface temperatures will remain above 35°F (2°C) for the next 24 hours. Avoid staining in direct sunlight or on hot surfaces. **FOR EXTERIOR USE ONLY.** Do not use on metallic, masonry, or interior surfaces.

PROTECT FROM FREEZING.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

PACKAGING

1-Gallon (3.78 L)
5-Gallon (18.9 L)

Not all products available in all sizes.

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *OLYMPIC*, *OLYMPIC* design, *WaterGuard*, *SunBlock*, *Scuff Guard* and *OLYMPIC MILDW CHECK* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



Olympic - US
PPG Architectural Finishes, Inc.
One PPG Place
Pittsburgh, PA 15272
www.olympic.com

Technical Services
1-800-426-6306

Architect/Specifier
1-888-PPG-IDEA

Olympic - Canada
PPG Canada, Inc.
4 Kenview Blvd
Brampton, ON L6T 5E4

T.D. 53201 2/2013
(Supersedes 9/2010)